

ADDENDUM No. 1

ADDENDUM DATE: 9/10/2025

ADDENDUM NUMBER: 1

RFP TITLE: Tow Contractor Services for Freeway Service Patrol Beats 1-5

ADDENDUM SUMMARY

The purpose of this Addendum is to provide additional information regarding an update to the Request for Proposals for Tow Contractor Services for Freeway Service Patrol Beats 1-5.

1. The attached tables below supplement and supersede the tow truck equipment requirements, required tools and required accessories listed the Freeway Service Patrol Scope of Work, Attachment A, section 4.

Standard Equipment Requirements - (x) indicates required

Item	Standard Equipment Requirements	Qty	Wrecker Tow Vehicle	Pickup / Service Vehicle
1	Mounted spotlight capable of directing a beam to both front and rear of vehicle (manual or electric is acceptable). 6 inch diameter lens (LED replaceable bulb type).	1	x	x
2	Overhead flashing amber lamps capable of 360 degrees illumination and being directed to the rear 180 degrees of vehicle only, with switches in cab directing the flashing amber warning lights. Metal mounting brackets are required for this light bar because antennae will be attached there.	1	x	x

3	Arrow stick mounted on the light pylon of the vehicle facing the rear. The "Traffic Advisor" must have the capabilities of directing to the right, left, and simultaneously to left and right.	1	x	x
4	Equipment capable of operating impact tools for tire removal purposes (pneumatic or electric)	1	Optional	Optional
5	Power outlets ("plug ins"). Front and rear mounted, with outlets compatible to 12-volt booster cables. (Service vehicles that use an external jumper battery unit are exempt)		x	x
6	Heavy duty, 60+ amp battery	1	x	x
7	Battery isolator between main battery and jumper battery or external jumper battery on service vehicle. External battery jumper shall be a 12-volt system with 2,000 peak amp (minimum).	1	x	x
8	Radio with the ability to communicate with the Contractor's base office.	1	x	x
9	Standard cab lighting.	1	x	x
10	Sufficient work lights to illuminate front & rear of vehicle to perform tasks as required during non-daylight hours.	1 Set	x	x
11	The vehicle shall be equipped with manufacturer's factory installed air conditioning and must be in good working order throughout the term of the contract.	1	x	x

12	All FSP vehicles are to be painted white for the purposes of this contract, unless the VCTC specifies a specific alternate color. The paint shall be in good condition on all parts of the truck to ensure a clean and professional appearance.		x	x
13	Class A Tow Truck with a minimum Gross Vehicle Weight Rating (GVWR) of 16,000 pounds and a maximum (not to exceed) of 26,000 pounds that can safely tow a 6,000 pound vehicle. This includes exceeding the tow trucks GVWR, front or rear axle weight rating, maximum tire weight ratings, or not maintaining 50% of the tow truck's un-laden weight on the front axle when lifting/carrying a load.		x	
14	Wheel lift or Self Loader towing equipment, with a minimum lift rating of 3,500 pounds. All tow equipment shall include proper safety straps.	1	x	
15	Boom with a minimum static rating of 16,000 pounds.	1	x	
16	Winch - Rated at a minimum of 8,000 pounds on the first layer of cable	1	x	
17	Winch Cable – 100 ft., 3/8 inch diameter (6X9) cable or OEM specification, with a working limit of 3,500 pounds.	1	x	
18	Safety chain D-ring or eyelet mounted on rear of truck.	1	x	
19	Tail lights/brake lights, portable remote with	1 set	x	

	extension cord or wireless (Drag lights)			
20	“Pop-up” type dolly and securement straps for removing otherwise un- towable vehicles	1	x	
21	Vehicles must be equipped with California Emissions package and will utilize a 1600 lb. minimum payload rating 4-door Pick-Up Truck (Must be crew cab, not extended/King Cab) and 4 x 2 single rear wheel axle chassis.			x
22	The vehicle shall have a minimum wheel base of 131.5 inches			x
23	The vehicle’s alternator shall have a minimum rated output of 100 amps and shall be equipped with a suitable solid-state voltage regulator.	1	x	x
24	The vehicle shall be equipped with an electronically controlled automatic transmission.	1		x
25	All tires, including full size spares, shall be steel belted radials and compatible in size and rating with the vehicle and its maximum rated load range. Mini spares shall meet all OEM load requirements and guidelines and shall not exceed maximum miles usage. All tires, including the spare, must be black walls.			x

26	The vehicle shall be equipped with a heavy duty, maintenance free, 12-volt battery (minimum rating of 600 cold cranking amps) or approved equal.	1		x
27	The vehicle shall be equipped with a minimum of power front disc brakes and power rear drum brakes with a four (4) wheel anti-lock brake system. Must be able to remove rear drum without removing rear axle.	1		x
28	The vehicle shall be equipped with power steering.	1		x
29	The vehicle shall be equipped with a 4-door crew-cab per manufacturer's standard.	1		x
30	The vehicle shall be equipped with an externally mounted, auxiliary transmission cooler, Hayden 1014 or approved equal.	1		Optional

FSP Required Tools - (x) indicates required

Item	Required Tools	Qty	Wrecker Tow Vehicle	Pickup / Service Vehicle
1	Hydraulic jack – 2 ton, floor, (lifting range 5 1/2" to 15 1/4"	1	x	x
2	Four way lug wrench (1 ASE.)	1	x	x
3	Four way lug wrench (1 metric) - (labeled or marked)	1	x	x
4	Impact gun (w/variable accessories)	1	Optional	Optional
5	Twenty-five (25') foot air hose (w/attachments). Two hoses are required.	2	x	x

6	Screwdrivers, Standard 1/8", 3/16", 1/4", 5/16"	1	x	x
7	Philips screw drivers head #1 and #2	1	x	x
8	Needle nose pliers	1	x	x
9	Adjustable rib joint pliers, 2" min. capacity	1	x	x
10	12" Open ended adjustable wrench	1	x	x
11	Sledge hammer minimum weight 4 lb.	1	x	x
12	Rubber hub cap mallet	1	x	x
13	Duct tape - roll of tape must be half full at a minimum	1	x	x
14	Tire gauge capable of registering up to 120 PSI	1	x	x
15	Mechanic's wire – minimum 20 feet	1	x	x
16	24" Adjustable bolt cutters	1	x	x
17	Wire cutters	1	x	x
18	Rubber wheel chock block 8"w x 4"h x 5"d	2	x	x
19	Hubcap and wheel-lock removal kit	1	x	x
20	Safety glasses	1	x	x

FSP Required Accessories - (x) indicates required

Item	Required Accessories	Qty	Wrecker Tow Vehicle	Pickup / Service Vehicle
1	Right and left side rear view adjustable exterior mirrors shall be original equipment from manufacturer (OEM).	1	x	x
2	An emergency reflector kit, Cats Eye Model 7500, KD 610-4645, or approved equal, shall be provided, but not mounted.	1	x	x

3	A Preco, Model 45AA, Solid State back-up alarm, or approved equivalent shall be provided. This alarm shall activate whenever the shift selector is placed in reverse gear.	1	x	x
4	Plastic or metal labeled "Gerry" containers (1) - 5 gallon or (2) - 2.5 gallon or (5) – 1 gallon in containers for each of the following: Diesel fuel – yellow, Unleaded fuel – red, Water – Blue. Must be CARB approved for fuel.	1, 2 or 5	x	x
5	First aid kit (small 5" x 9")	1	x	x
6	Fire extinguisher – aggregate rating of at least 4-B,C with current inspection tag attached (Extinguisher shall be secured in truck and labeled at location of truck)	1	x	x
7	Pry bars – 36" or longer	1	x	x
8	24" wide street broom in serviceable condition	1	x	x
9	Square nose shovel	1	x	x
10	Highway flares, (15 minute)	12	x	x

11	Traffic cones with company identification. Traffic cones shall be fluorescent and of good commercial quality, flexible material suitable for the purpose intended. The outer section of the portion above the base of the cone shall be translucent and be of a highly pigmented fluorescent orange polyvinyl compound. The overall height of the cone shall be at least 28 inches and the bottom inside diameter shall not be less than 10.5 inches. The base shall be of sufficient weight and size such that the traffic cone will remain in an upright position. Traffic cones shall be affixed with double band reflective cones sleeves with 2 white reflective bands. The top band shall be 6 inches high, placed a maximum of 4 inches from the top of the cone. The lower band shall be 4 inches high, placed 2 inches below the bottom	6	x	x
12	Air Compressor is required on all FSP vehicles	1	x	x
13	Rechargeable flashlight and/or flashlight w/spare batteries	1	x	x
14	Booster cables, 25 foot minimum length, 3- gauge copper wire with heavy-duty clamps and one end adapted to truck power outlet (service vehicles with external jumper batteries are exempt)	1	x	x
15	Funnel	1	x	x

16	5-gallon can with lid filled with sand or other absorbent granular material	1	x	x
17	Lock out set	1	x	x
18	Trash can with lid (5 gallon)	1	x	x
19	Snatch block with hook, rated for 4 tons minimum	1	x	
20	Two (2) safety chains minimum 10 feet each (minimum grade 70)	2	x	
21	4" x 6" x 12" wooden cross beam	1	x	
22	Trailer hitch capable of handling a 1 7/8 in. ball, and 2 in. ball required. The trailer ball is required as part of the hitch.	1	x	
23	Utility straps (for use as utility or miscellaneous straps)	2	x	